

ALV2 (ALVB) series/ Peripherals

# Elevator Card Reader



Elevator card reader  
RDFL-B03H/RDFL-B03BLE

- Only the guests with a valid card keycard will have access to the elevators / floors.
- Reader is designed to be built into elevator panel.
- Up to 40 contacts relays available.
- Up to 4 card readers can be operable under one controller.
- ALVB Available with Mobile key option.

---

## MIWA LOCK CO., LTD.

JAPAN 3-1-12, Shiba, Minato-ku, Tokyo 105-8510  
URL : [www.miwa-lock.biz](http://www.miwa-lock.biz)

U.S.A 9272 Jeronimo, Suite 119, Irvine CA 92618  
URL : [www.miwalock.com](http://www.miwalock.com)

# Specifications

## Elevator card reader

External dimensions	W116mm× H120mm× D45mm
Weight	250g
Power supply	Supplied from controller
Environmental condition	-5℃~+50℃/20~90%RH (No condensation)

## Elevator reader controller

External dimensions	W374mm × H314mm × D115mm
Weight	6kg (without back-up battery)
Power supply	AC100V ~ 240V ± 10%
Power consumption	75VA
Output	Normal open or close contact Max 40 relays
Duration of contact	1 ~ 59 sec. adjustable
Contact capacity	DC30V / 2A · AC250V / 2A
Environmental condition	Internal installation only 0℃~+50℃/20~80%RH (No condensation)

# Detail Drawing

CMHL-401/402/403/404

RDFL-B03H/RDFL-B03BLE

